

ACOUSTIC CEMENT BOND TOOL



The Acoustic Cement Bond Tool (ACBT) is a cement bond evaluation tool equipped with 2 transmitters (T1, T2) and 2 receivers (R1, R2) of acoustic waveforms. Pairs of emitters and receivers form two measurement bases with opposite observation systems of acoustic response. The ACBT delivers detailed information about the well isolation condition achieved by the cementing job. The tool provides measurements in oil and gas wells with the diameter of the wellbore up to 8.7" (220mm).

Applications

- Cement bond quality evaluation
- Acoustic profile in open hole wells

Advantages

- Memory mode and Surface Readout
- Compatible with an entire range of North Side Tools

Tool Specifications	
Probes configuration	R20.4R11.0T10.4T2
Interval time of elastic wave propagation	100-500 μ s/m (\pm 3%)
Casing Diameter	3.5-7.0 in (89-178 mm)
Borehole diameter	3.3-8.7 in (85-220 mm)
Transmitter operation frequency	20 kHz
Maximum Operating Temperature	150°C (302°F)
Maximum Operating Pressure	11,600 PSI (80 MPa)
Tool length	14.8 ft (4.5 m)
Tool OD	2.4 in (60 mm)
Tool weight	95 lbs (43 kg)
Surface read-out / Memory	Both
Operational time in memory mode	24 hrs
H ₂ S resistance	6% standard

